

## [Features]

- **High contrast(600:1)**
- **16.77M/262K colors (LVDS RGB 8-bit/6-bit)**
- **Reversible-scan direction**
- **Long-life LED backlight built-in LED driver\*<sup>1</sup>**



Pixel	1024(H) x 768(V)
Display area	304.128(H) x 228.096(V) mm 15.0inch (38cm)
Display color	16,777,216 colors/ 262,144 colors
Pixel pitch	0.297(H) x 0.297(V) mm
Luminance	400cd/m <sup>2</sup> (typ.)
Contrast ratio	600:1 (typ.)
Viewing angle* <sup>2</sup>	Up: 80°,Down: 80°,Left: 80°,Right: 80°
Response time* <sup>3</sup>	8ms (typ.)
Signal system	LVDS 1-port RGB 8-bit/6-bit
Power supply voltage	LCD signal processing board:3.3V, LED driver:12.0V
Power consumption	7.8 W (typ.)
Operating temperature	-20°C to +70°C
Storage temperature	-30°C to +80°C
Polarizer surface	Antiglare
Module size	W 326.5 (typ.) x H 253.5 (typ.) x D 12.1 (max.) mm
Weight	1050g (typ.)
Backlight	LED backlight(Replaceable)
LED driver	Built in

\*<sup>1</sup> 100k hours long life LED

\*<sup>2</sup> Contrast ratio ≥ 10:1

\*<sup>3</sup> Ton+Toff (10%←→90%)

\*All information is subject to change without notice.

\*Screen images are simulated.

<Tianma Japan web site>

Japanese <https://www.tianma.co.jp/jp>

English <https://www.tianma.co.jp/en>

Published date: Jul. 2017  
©Tianma Japan, Ltd. 2017