

[Features]

- Wide viewing angle
- LVDS interface
- Selectable 8-bit or 6-bit digital signals for data of RGB
- Reversible-scan direction
- Narrow border
- Thin structure
- LED backlight built in LED driver
- Replaceable lamp for backlight



Pixel	1,024(H) x 768(V)
Display area	304.128(H) x 228.096(V) mm (15.0inch (38cm) diagonal)
Display color	16,194,277 colors/ 262,144 colors
Pixel pitch	0.297(H) x 0.297(V) mm
Luminance	500cd/m ² (typ.)
Contrast ratio	1,000:1 (typ.)
Viewing angle ^{*1}	Up: 80°,Down: 80°,Left: 80°,Right: 80°
Response time ^{*2}	8ms (typ.)
Signal system	LVDS 1-port RGB 8-bit/6-bit
Power supply voltage	LCD signal processing board:3.3V, LED driver:12.0V
Power consumption	8.5W (typ.)
Operating temperature	-20°C to +70°C
Storage temperature	-20°C to +70°C
Polarizer surface	Antiglare
Module size	W 326.5 (typ.) x H 253.5 (typ.) x D 6.8 (max.) mm
Weight	640g (typ.)
Backlight	LED backlight (Replaceable)
LED driver	Built in

*1: Contrast ratio ≥ 10:1

*2: Ton+Toff (10%←→90%)

*All information is subject to change without notice.

*Screen images are simulated.

<Tianma Japan web site>

Japanese <https://www.tianma.co.jp/jp>

English <https://www.tianma.co.jp/en>

Published date: Feb. 2019

©Tianma Japan, Ltd. 2019