


[Features]

- High contrast (900:1)
- 262K colors (CMOS RGB 6-bit)
- Reversible-scan direction
- Wide temperature (-30°C to +80°C)
- Long-life LED backlight^{*1}



Pixel	800 (H) x 600 (V)
Display area	246.0 (H) x 184.5 (V) mm 12.1inches (31cm)
Display color	16,777,216 colors/ 262,144 colors
Pixel pitch	0.3075 (H)x0.3075 (V) mm
Luminance	450cd/m ² (typ.)
Contrast ratio	900:1 (typ.)
Viewing angle*2	Up: 80°, Down: 80°, Left: 80°, Right: 80°
Response time*3	18ms (typ.)
Signal system	LVDS 1-port RGB 8-bit/6-bit
Power supply voltage	3.3V
Power consumption	4.9W (typ.)
Operating temperature	-30°C to +80°C
Storage temperature	-30°C to +80°C
Polarizer surface	Clear
Module size	W 280.0 (typ.) x H 210.0 (typ.) x D 9.6 (max.) mm
Weight	580g (typ.)
Backlight	LED backlight (Replaceable)
LED driver	121PW02F

*1: 70k hours long life LED

*2: Contrast ratio ≥ 10:1

*3: Ton+Toff (10%←→90%)

*All information is subject to change without notice.

*Screen images are simulated.

<Tianma Japan web site>

Japanese <https://www.tianma.co.jp/jp>

English <https://www.tianma.co.jp/en>

Published date: Jul. 2017
©Tianma Japan, Ltd. 2017